



- **Stainless steel interior and exterior, aluminum back.**
Option of bright white aluminum interior available.
- **Refrigeration system** keeps food at safe temperatures between 33°F and 41°F (0.5°C to 5°C).
- **Self-Closing doors with locks 90 degree stay-open feature**
- **Shelves:** Adjustable heavy-duty PVC coated shelves.
- **Electronic control system** makes it easy to adjust temperature set point and defrost frequency.
- **Preinstalled heavy-duty casters with brakes.**
- **Removable installation board** makes it easy to access condenser coil for cleaning and service.
- **These units use HYDRO-CARBON R290 refrigerant,** which is environmentally friendly and more efficient than R134a/R404a refrigerant.

Reach-in Solid Door Refrigerators - ERS-R Series



ERS-23R-HC



ERS-48R-HC



ERS-72R-HC

MODEL	DOORS	SHELVES	DIMENSIONS - WxDxH inches	CAPACITY cu.ft.	HP	AMPS	VOLTAGE	PLUG TYPE
ERS-23R-HC	1	3	29 x 32 1/4 x 82 1/2	23	1/5	2.6	115/60/1	NEMA 5-15P
ERS-48R-HC	2	6	54 x 32 1/4 x 82 1/2	47	1/4+	4.3	115/60/1	NEMA 5-15P
ERS-72R-HC	3	9	80 9/10 x 32 1/4 x 82 1/2	72	3/4	9.1	115/60/1	NEMA 5-15P



Specifications subject to change without notice.

ENHANCED
REFRIGERATION

2610 E. Woodward Ave. Fresno, Ca. 93721
Email: customerservice@enhancedequipment.com
Phone (720) 309-1902

WARRANTY

5 Year Compressor
2 Year Parts and Labor