



Product Specification Sheet - GPSS90

GPSS90	Rectangular Diner Platter, S/S, 9.5 x 6.5 x 1.75" Brick Pattern				
---------------	---	--	--	--	--

Country of Origin	IN	Harmonized Tariff Code	7323.93.0060	Minimum Order Quantity	1 EA
--------------------------	----	-------------------------------	--------------	-------------------------------	------

Item Specifications

Individual Unit	Length	Width	Height	Piece Weight	0.617 (lbs)	0.280 (kg)	UPC Label on Product?	Yes
	9.75 (in)	6.75 (in)	1.75 (in)	Unit Measure Net Weight	0.617 (lbs)	0.280 (kg)	UPC Application	Label
	25 (cm)	17 (cm)	4.5 (cm)	Unit Measure Gross Weight	0.740 (lbs)	0.336 (kg)	BPA Free	Yes
	Min. Temp.	32 (°F)	0 (°C)	Individual Unit Cube	0.0378 (ft³)	0.00107 (m³)	NSF	No
	Max Temp.	190 (°F)	88 (°C)	Capacity	()	()	Dishwasher Safe	No
							Microwave Safe	No

Component	Material	ItemNumber	Material Detail	Origin	Gauge	Diameter	Weight
Platter	Stainless Steel (200 Series)		Matte Finish Brick Design	India	0.4 (mm)		280 (g)
Reinforcing Wire	Stainless Steel (200 Series)						

Packaging and UPC Information

	Packaging	Quantity	Length	Width	Height	Weight	Cube	Plastic Waste	Paper Waste	UPC
Piece Packaging	Poly Bag	1 EA	9.8125 (in) 24.9 (cm)	6.8125 (in) 17.3 (cm)	1.8125 (in) 4.6 (cm)	0.642 (lbs) 0.3 (kg)	0.07 (ft³) 0.002 (m³)			727875197238
Inner Carton	5 Ply Corrugated Carton	12 EA	10.25 (in) 26.0 (cm)	7.125 (in) 18.1 (cm)	9.25 (in) 23.5 (cm)	8.384 (lbs) 3.8 (kg)	0.39 (ft³) 0.011 (m³)			10727875197235
Master Carton	5 Ply Corrugated Carton	36 EA	10.75 (in) 27.3 (cm)	9.75 (in) 24.8 (cm)	22.5 (in) 57.1 (cm)	26.65 (lbs) 12.0 (kg)	1.36 (ft³) 0.039 (m³)			30727875197239

Pallet Specifications

TI (cartons/layer)	18	HI (layers/pallet)	3	Total Cartons	54	Total Units	1944	Pallet Height	35 (in)
---------------------------	----	---------------------------	---	----------------------	----	--------------------	------	----------------------	---------

Product Notes	Packaging Details
	An easy peel piece UPC label is applied to the underside of each platter then each platter is placed into a poly bag. Poly bags require two punched holes and multilingual suffocation warnings. There are 12 Each per inner (5 Ply Carton) and 36 Each per master (5 Ply Carton). Two UPC labels are applied to adjacent corners of each inner and master carton.

