

Hamilton Beach
COMMERCIAL

BigRig™

Family of Immersion Blenders



Incredibly
FAST
Results

Blend, chop,
mix, puree,
and emulsify

Most powerful motor in its class*

Comfortable 2-position handle and ergonomic shaft grip

Variable speed ThumbDrive™ with color-coded light for immediate feedback

100% sealed, removable stainless steel shaft

Continuous run operation for high-volume blending

Serviceable 12 ft./365cm power cord designed for high visibility

Assurance with 2 year replacement warranty

* 800 watts for 120V; 1000 watts for 220-240V

Various Sizes Available



Interchangeable Shaft

12"/305mm, 14"/355mm, 16"/406mm,
18"/457mm, and 21"/533mm
(sold separately)

For more Good Thinking® visit hamiltonbeachcommercial.com






Stainless Steel Shaft with Ergonomic Grip
Detaches to let you change to a different-size shaft

Blend Volume Chart

12"/305mm shaft - up to 6 gal. (23 L)
14"/355mm shaft - up to 14 gal. (53 L)
16"/406mm shaft - up to 23 gal. (87 L)
18"/457mm shaft - up to 32 gal. (121 L)
21"/533mm shaft - up to 42 gal. (158 L)



Stainless Steel Blade with Guard
Blends, chops, purees, or emulsifies ingredients quickly



Optional 10"/25cm Whisk
Lets you whip and aerate ingredients (sold separately)



ThumbDrive™ Variable Speed Dial
With color-coded light for immediate feedback about blender status

Patent-Pending Serviceable Cord
Helps extend the blender's life



Ergonomic Design with Light-Touch Controls
Offers multiple hand positions for comfort



Wall Mount and Cord Holder
For neat, easy storage

IMMERSION BLENDER SERIES

SPECIFICATIONS:

	8.5" (21.6 cm)	5.5" (14 cm)				Whisk only
	30.5" (78 cm)	32.5" (82 cm)	34.5" (88 cm)	36.5" (93 cm)	39.5" (100 cm)	19.5" (49 cm)
	HMI012	HMI014	HMI016	HMI018	HMI021	HMI02W
Shipping Weights:						
lbs	13.5	13.7	13.9	14.1	15.2	6.0
kg	6.1	6.2	6.3	6.4	7.0	2.7

Standard: unit comes with power base, stainless steel shaft, and wall-mount hanger

Controls: Variable speed dial, trigger, power button

Warranty: 2 year parts & labor

Blend speeds: min. 3,000 rpm - max. 15,000 rpm

HMI (120V)

120V~, 60 Hz, 800 W



US only



HMI-CE/-UK (230V)

220-240V~, 50-60 Hz, 1000 W, IPX1

