

# PASS-THRU GLASS/HALF GLASS DOOR REF. NATURAL Refrigerant

**Self-Cleaning Condenser Equipped Units**

■ **Self-Cleaning Condenser (Patented)**

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ **Digital temperature control & monitor system**

- Keeps food products safe by maintaining constant temperatures
- Alarms that sound when doors are not sealed shut; protects against food spoilage that originates from cold air leaks
- Early warning alarm program detects issues before malfunction occurs
- Digital display allows for easy monitoring
- Programs interpret the condition of refrigeration systems by self-diagnosis
- Rapid cool-down function (Turbo Cooling)
- Automatic evaporator fan motor delays

■ **Hydrocarbon refrigerants (R-290)**

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ **Cold air distribution system**

Provides uniformly maintained temperature within the food zone.

■ **Hot gas condensate system**

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

■ **All stainless steel cabinet construction**

The PRO series model boasts a stainless steel interior and a 22 gauge stainless steel exterior (galvanized steel top, bottom). It guarantees the utmost in cleanliness and long product life. The PRO series model adds a touch of style to the most refined setting.

■ **Sturdy, clean stainless steel shelving**

Shelves are the most important part of cleanliness as they come in direct contact with food. After a while, PVC coated wire shelves may peel, rust and lead to unsanitary conditions. Only the Turbo Air PRO series uniquely provides stainless steel shelving.

■ **LED interior lighting**

■ **Thermostatic expansion valves**

■ **High-density polyurethane insulation**

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Maintenance free,  
Self-Cleaning Condenser



PRO-26R-G-PT-N

PRO-50-4R-G-PT-N

■ **Left hinged (PRO-26R-G-PT-N-L, PRO-26-2R-G-PT-N-L), front left hinged & back right hinged (PRO-26-2R-G-PT-LR), front right hinged & back left hinged (PRO-26-2R-G-PT-RL) models available**

■ **Refrigerator holds 33°F ~ 38°F for the best in food preservation**

■ **Standard features**

- Top mount compressor
- USB temperature data storage
- Anti-corrosion coated evaporator
- Easily replaceable one-piece magnetic door gaskets
- Self-contained system
- Solid and sturdy grille design
- Door locks
- 4" dia. swivel casters with locks on the front set
- Lead time applies

■ **Optional features**

- Legs available for all models
- Tray slides available

## PRO-R-G-PT MODELS SPECIFICATIONS

ELECTRICAL DATA	PRO-26R-G-PT-N	PRO-50R-G-PT-N	PRO-26-2R-G-PT-N	PRO-50-4R-G-PT-N
Voltage	115/60/1	115/60/1	115/60/1	115/60/1
Plug Type	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P	Ⓢ NEMA 5-15P
Full Load Amp.	7.0	8.0	7.0	8.0
Compressor HP	1/2	1/2	1/2	1/2
Feed Wires with Ground	3	3	3	3
Cord Length (ft.)	9	9	9	9
Refrigerant	R-290	R-290	R-290	R-290
<b>DIMENSIONAL DATA</b>				
Net Capacity (cu. ft.)	29.01	54.82	27.52	50.23
Ext. Dimension (L x D x H†) (in.)	28 <sup>3</sup> / <sub>4</sub> x 36 <sup>1</sup> / <sub>4</sub> x 78	51 <sup>3</sup> / <sub>4</sub> x 36 <sup>1</sup> / <sub>4</sub> x 78	28 <sup>3</sup> / <sub>4</sub> x 36 <sup>1</sup> / <sub>4</sub> x 78	51 <sup>3</sup> / <sub>4</sub> x 36 <sup>1</sup> / <sub>4</sub> x 78
Int. Dimension (L x D x H) (in.)	23 <sup>7</sup> / <sub>8</sub> x 27 <sup>5</sup> / <sub>8</sub> x 58 <sup>3</sup> / <sub>4</sub>	46 <sup>3</sup> / <sub>4</sub> x 27 <sup>5</sup> / <sub>8</sub> x 58 <sup>3</sup> / <sub>4</sub>	23 <sup>7</sup> / <sub>8</sub> x 27 <sup>5</sup> / <sub>8</sub> x 58 <sup>3</sup> / <sub>4</sub>	46 <sup>3</sup> / <sub>4</sub> x 27 <sup>5</sup> / <sub>8</sub> x 58 <sup>3</sup> / <sub>4</sub>
# of Doors	2	4	4	8
# of Racks Accepted	1	2	1	2
# of Shelves (Size (L x D) (in.))	3 (23 <sup>1</sup> / <sub>2</sub> x 26 <sup>3</sup> / <sub>8</sub> )	6 (22 <sup>3</sup> / <sub>4</sub> x 26 <sup>3</sup> / <sub>8</sub> (L/R))	3 (23 <sup>1</sup> / <sub>2</sub> x 26 <sup>3</sup> / <sub>8</sub> )	6 (22 <sup>3</sup> / <sub>4</sub> x 26 <sup>3</sup> / <sub>8</sub> (L/R))
Net Weight (lbs.)	379	583	360	611
Gross Weight (lbs.)	422	646	416	674

Design and specifications subject to change without notice. Most updated spec sheets are available at [www.turboairinc.com](http://www.turboairinc.com).

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 2-1/2" for door handles. † Height does not include 5" for caster height.

■ **WARRANTY: 3 Year Parts and Labor Warranty, Additional 4 Year Warranty on Compressor**